

## EEV-EX13



Micro ATX Com Express Carrier Board, accept Avalue and other COM Express T type 2 compatible CPU Modules, VGA, LVDS, Audio Interface, 1x CF, 1x PCI, 2x PCIe x1, 1x PCIe x16, 4x SATA, 2x COM, 8x USB, 8-bit GPIO, Express Card (54mm), T type 2 Pin-out

### Avalue

#### System

Festplatte                      One CompactFlash Type I/II socket

#### Schnittstelle Rückseite

USB	4
RS 232/422/485	1
Parallel	1
VGA	1
Audio Mic In	1
Audio In	1
Audio Out	1

## Onboard Schnittstellen

USB	4
RS 232	1
LVDS Kanal	1
Digital IO	8-bit GPIO
IDE	1
SATA	4
CompactFlash Sockel	1

## Slots

PCI Express x1	2
PCI Express x16	1
PCI	1
Express Card	1

## Audio

Chipsatz	Realtek® - ALC883
----------	-------------------

## Betriebsbedingungen

Breite	244 mm
Tiefe	244 mm
Gewicht	1 kg
min. Betriebstemperatur	0 °C
max. Betriebstemperatur	60 °C
Feuchtigkeit	0 ~ 90% relative humidity, non-condensing