

EEV-EX14



Micro ATX COM Express Type 6 Carrier Board, accept Avalue and other COM Express Type 6 compatible CPU Modules, VGA, LVDS, HDMI, DisplayPort, Audio Interface, 1x PCIe x16, 1x PCIe x4, 1x PCIe x1, 4x SATA, 2x COM, 8x USB (Up to 4 USB 3.0), 8-bit GPIO, Mini-PCle Card with SIM Card Slot, Express Card (54mm), Type 6 Pin-out

[Avalue](#)

System

BIOS Carrier Board BIOS SPI ROM

Schnittstelle Rückseite

USB	4
RS 232/422/485	1
Parallel	1
PS/2	2
VGA	1
HDMI	1
Display Port	1
Audio Mic In	1
Audio In	1
Audio Out	1
RJ45	2

Onboard Schnittstellen

USB	8
RS 232	1
Digital IO	8-bit GPIO
SATA	4

Slots

PCI Express x1	1
PCI Express x4	1
PCI Express x16	1
mini PCI Express	1
Express Card	1

Audio

Chipsatz	Realtek® - ALC892
----------	-------------------

Betriebsbedingungen

Breite	244 mm
Tiefe	244 mm
Gewicht	1 kg
min. Betriebstemperatur	0 °C
max. Betriebstemperatur	60 °C
Feuchtigkeit	0 ~ 90% relative humidity, non-condensing