

Cat6 KVM - NEU



Cat6 KVM with 8, 16 or 32 ports in 1U, Cat6 dongle available for DP, HDMI, DVI-D or VGA video input, Local console & KVM ports support resolution up to 1920 x 1200, Port switching via OSD, front button & keyboard hotkeys, Multi lingual OSD menu, Hot pluggable, no software or drivers required, Multi-platform for PC, server, Blade Server & SUN / MAC, Cascade levels up to 8 KVM switches

Port #: 8, 16 or 32

Connector: RJ-45

Connectivity: DP / HDMI / DVI-D / VGA dongle via Cat6 / Cat5 cable to server up to 40 meters (132 feet)

Resolution: 16:10 - max. 1920 x 1200 / 16:9 - max. 1920 x 1080 / 4:3 - max. 1600 x 1200

[Austin Hughes \(detailliertes Herstellerdatenblatt\)](#)

System

Betriebssystem	Windows / Linux / Unix / Mac OS
----------------	---------------------------------

Schnittstelle Vorderseite

VGA	1
-----	---

Schnittstelle Rückseite

USB	2
-----	---

RJ45	32
------	----

Betriebsbedingungen

Breite	443 mm
Höhe	44 mm
Tiefe	171 mm
max. Schläge	10G acceleration (11ms duration)
max. Vibration	10~300Hz 0.5G RMS random vibration
Gewicht	3 kg
min. Betriebstemperatur	0 °C
max. Betriebstemperatur	55 °C
Eingangsspannung	100 - 240 V
Stromverbrauch	22 W
Zertifikate	cUL, FCC & CE certified / RoHS2 & REACH compliant
Feuchtigkeit	operating: 20~90%, non- condensing / 5 ~90%, non- condensing