

# Matrix Cat6 KVM - NEU



Cat6 KVM with 16 or 32 ports in 1U,  
Simultaneous & independent access up to 4  
consoles, Cat6 dongle available for DP, HDMI,  
DVI-D or VGA video input, Local console & KVM  
ports support resolution up to 1920 x 1080, Port  
switching via OSD, front button & keyboard  
hotkeys, Multi lingual OSD menu, Hot pluggable,  
no software or drivers required, Multi-platform  
for PC, server, Blade Server & SUN / MAC,  
Cascade levels up to 8 KVM switches

Port #: 16 or 32

Connector: RJ-45

Connectivity: DP / HDMI / DVI-D / VGA dongle via  
Cat6 / Cat5 cable to server up to 40 meters  
(132 feet)

Resolution: 16:9 - max. 1920 x 1080 / 4:3 - max.  
1600 x 1200

[Austin Hughes \(detailliertes Herstellerdatenblatt\)](#)

## System

Betriebssystem Windows / Linux / Unix / Mac  
OS

## Schnittstelle Rückseite

|      |    |
|------|----|
| USB  | 2  |
| VGA  | 1  |
| RJ45 | 32 |

## Betriebsbedingungen

|                         |                                                         |
|-------------------------|---------------------------------------------------------|
| Breite                  | 443 mm                                                  |
| Höhe                    | 171 mm                                                  |
| Tiefe                   | 44 mm                                                   |
| max. Schläge            | 10G acceleration (11ms duration)                        |
| max. Vibration          | 10 - 300Hz 0.5G RMS random vibration                    |
| Gewicht                 | 3 kg                                                    |
| min. Betriebstemperatur | 0 °C                                                    |
| max. Betriebstemperatur | 55 °C                                                   |
| Eingangsspannung        | 100 - 240 V                                             |
| Stromverbrauch          | 34 W                                                    |
| Zertifikate             | cUL, FCC, CE   RoHS2 & REACH                            |
| Feuchtigkeit            | Operating: 20 - 90%   Storage: 5 - 90% (non-condensing) |

## Gehäuse

|              |            |
|--------------|------------|
| Beschreibung | Dark Steel |
|--------------|------------|

## Display

|                  |      |
|------------------|------|
| Auflösung Breite | 1920 |
| Auflösung Höhe   | 1080 |