

RM1045



10.4" Rack Mount LED Monitor, 800 x 600, 350 cd/m², 1x VGA

optional: resistive touch, capacitive touch, saw touch, infrared touch, protected glass

Winsonic

Schnittstelle Rückseite

VGA	1
Audio Out	1

Audio

Lautsprecher	2x 2W
--------------	-------

Betriebsbedingungen

Breite	482 mm
Höhe	200 mm
Tiefe	116 mm
Gewicht	5 kg
min. Betriebstemperatur	0 °C
max. Betriebstemperatur	50 °C
Eingangsspannung	AC 90 - 260 V
Stromverbrauch	(max.) 11 W
Zertifikate	FCC, CE
Feuchtigkeit	10 ~ 90% (non-condensing)

Display


Zoll	10.4 "
Auflösung Breite	800
Auflösung Höhe	600
Lumen	350 cd / m ²
Hintergrundbeleuchtung	LED
MTBF	35000 h ²
Farben	262000
Kontrast	400 : 1

Mounting

VESA 75 x

Wandbefestigung x

Technische Zeichnungen



Zubehör

Rack Mount Metal 3mm

Rack Mount Metal 3mm

1x DVI

optional 1x DVI

OEM Infrarot / Infrared Touch

optional: OEM Infrarot Touch

Projizierter Kapazitiver Touch / Projected Capacitive Touch

optional: Projizierter Kapazitiver Touch / Projected Capacitive Touch

Resistiver Touch / Resestive Touch

optional: Resistiver Touch / Resestive Touch

Resistiver Touch (ELO) / Resestive Touch (ELO)

optional: Resistiver Touch (ELO) / Resestive Touch (ELO)

RS-232 Remote Control F2482

optional: RS-232 Remote Control, only for F2482

RS-232 Remote Control SE98X

optional: RS-232 Remote Control, only for SE98X

SAW Touch

optional: SAW Touch

SAW Touch (ELO)

optional: SAW Touch (ELO)

SAW Touch 6mm Anti-Vandalismus / Anti-Vandalism

optional: SAW Touch 6mm Anti-Vandalismus / Anti-Vandalism

Verspiegelung / Mirroring

optional: Verspiegelung / Mirroring

1x DVI + AV + Looping

optional: 1x DVI + AV + Looping

HD-SDI (High Definition Serial Digital Interface) Receiver

optional: HD-SDI (High Definition Serial Digital Interface) Receiver

HD-SDI (High Definition Serial Digital Interface) Receiver + Looping

optional: HD-SDI (High Definition Serial Digital Interface) Receiver + Looping

SV + AV

optional: SV + AV

Networking Digital Signage 480p

optional: Networking Digital Signage 480p

Networking Digital Signage 720p/1080p

optional: Networking Digital Signage 720p/1080p

1x DVI + 1x HDMI

optional: 1x DVI + 1x HDMI

24V DC-IN

optional: 24V DC-IN

Anti Reflektion Glas / Anti-Reflection Glas 3mm

optional: Anti Reflektion Glass 3mm

Anti Reflektion Glas / Anti-Reflection Glas 6mm (Anti-Vandalismus / Anti-Vandalism)

optional: Anti Reflektion Glass 6mm (Anti-Vandalismus)

Auflösung / Resolution: max. 720p

optional: Auflösung/Resolution: max. 720p

Color Graphics Adapter

optional: Color Graphics Adapter

Externe / External OSD - Box

optional: Externe OSD - Box

Kapazitiver Touch / Capacitive Touch

optional: Kapazitiver Touch / Capacitive Touch

Kapazitiver Touch / Capacitive Touch (3M)

optional: Kapazitiver Touch / Capacitive Touch (3M)

LED - Backlight - 1000cd/m²

optional: LED - Backlight - 1000cd/m²

LED - Backlight - 700cd/m²

optional: LED - Backlight - 700cd/m²

Light Sensor

optional: Light Sensor

Motion Sensor

optional: Motion Sensor

1x DVI + SV + AV

optional: SV+ AV+ 1x DVI
