



1U 19" LCD drawer, short depth design of 500mm (19.7"), depth will suit a 600mm rack application, sliding LCD allowing LCD to remain open when the rack door is closed, installation slides for easy and quick installation, enhanced aesthetics with molded front panel and two point lock

Options:

- o 17" / 19" Touchscreen: capacitive, resistive
- o S-Video + Composite (BNC)
- o HDMI or Audio input
- o 48V, 24V oder 12VDC power

Betriebsbedingungen

Breite	588 mm
Höhe	758 mm
Tiefe	120 mm
max. Schläge	10G peak acceleration (11m sec. duration)
max. Vibration	5 ~ 500Hz (3 axes), 1G PTP
Gewicht	13 kg
min. Betriebstemperatur	1 °C
max. Betriebstemperatur	50 °C
Eingangsspannung	AC 100 ~ 240 V
Stromverbrauch	(max.) 48 W
Zertifikate	FCC, CE
Feuchtigkeit	5 ~ 90% (non-condensing)

Display

Zoll	19 "
Auflösung Breite	1280
Auflösung Höhe	1024

Lumen	250 cd / m ²
Hintergrundbeleuchtung	LED
Blickwinkel	170
MTBF	30000 h ²
Farben	16700000
Kontrast	1000 : 1

Technische Zeichnungen

Diagrams (mm)

