



6U rackmount 17" widescreen LCD, support Full HD with 1080p resolution, 1.07 Billion true colors - 10-bit, PIP & Picture by Picture viewing efficiency, Green LED-backlit panel technology, ideal für CCTV security & industrial control

Options

- 3G / HD / SD-SDI Broadcast-grade input (w/ speaker)
- MCS Multi-display control solution
- F17" Touchscreen : Resistive
- HDMI, S-Video + Composite (BNC) or Audio input
- 48V, 24V or 12V DC power
- MIL-typ or lockable connector

Betriebsbedingungen

Breite	480 mm
Höhe	48 mm
Tiefe	266 mm
max. Schläge	10G peak acceleration (11m sec. duration)
max. Vibration	5 ~ 500Hz (3 axes), 1G PTP
Gewicht	5 kg
min. Betriebstemperatur	1 °C
max. Betriebstemperatur	50 °C
Eingangsspannung	AC 100 ~ 240 V
Stromverbrauch	(max.) 48 W
Zertifikate	FCC, CE
Feuchtigkeit	5 ~ 90% (non-condensing)

Display

Zoll	17.3 "
Auflösung Breite	1920
Auflösung Höhe	1080
Lumen	300 cd / m ²
Hintergrundbeleuchtung	LED
Blickwinkel	187
MT BF	20000 h ²
Farben	1070000000
Kontrast	600 : 1

Diagrams (mm)

