

## RP-F821 - NEU



8U 21" LCD display panel, 1920 x 1080 native resolution / 16.7M colors, DVI-D + VGA video input, PIP Sub-screen & PBP Dual-screen viewing efficiency, 2-year standard warranty ( upgradable up to 5 years )

Options:

- HDMI 1.3 video input
- 3G / HD / SD-SDI Broadcast-grade input
- S-Video + Composite ( BNC )
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MCS Multi display OSD controller
- MIL-type or lockable connector
- Touchscreen : Capacitive 1-pt / Resistive 1-pt

[Austin Hughes](#)

### Schnittstelle Rückseite

VGA	1
DVI	1

### Betriebsbedingungen

Breite	502 mm
Höhe	353 mm
Tiefe	64 mm
max. Schläge	10G acceleration ( 11ms duration )
max. Vibration	10~300Hz 0.5G RMS random vibration
Gewicht	9 kg
min. Betriebstemperatur	0 °C
max. Betriebstemperatur	55 °C
Eingangsspannung	AC 100 - 240 V
Stromverbrauch	32 W
Zertifikate	FCC, CE / LVD, RoHS2, REACH
Feuchtigkeit	20 - 90% non-condensing

## Display

Zoll	21.5 "
Auflösung Breite	1920
Auflösung Höhe	1080
Lumen	250 cd / m <sup>2</sup>
Hintergrundbeleuchtung	LED
Blickwinkel	85
MTBF	30000 h <sup>2</sup>
Farben	16700000
Kontrast	1000 : 1
Touchtypen	1-pt capacitive / resistive Touch Screen (optional)

## Mounting

Rackmount	<input type="checkbox"/>
-----------	--------------------------