

UltraView DP-12" 4:3 LED

12" 4:3 Panel Mount LED Monitor, 800 x 600, 450 cd/m², 1x VGA



optional: Resistive/Capacitive Touch, Universal open frame model (OP-12), Embedded Video Management & Transmission over Network Modules, DC Power

[Austin Hughes](#)

Schnittstelle Rückseite

VGA	1
DVI	optional
HDMI	optional
S-Video	optional
BNC	optional
Audio In	1
Audio Out	1

Betriebsbedingungen

Breite	314 mm
Höhe	255 mm
Tiefe	64 mm
max. Schläge	10G acceleration (11m duration)
max. Vibration	10~300Hz 0.5 RMS random vibration
Gewicht	3 kg
min. Betriebstemperatur	0 °C
max. Betriebstemperatur	55 °C

Eingangsspannung	AC 100 ~ 240 V
Stromverbrauch	14 W
Zertifikate	CE, FCC, LVD, RoHS2, REACH
Feuchtigkeit	20 ~ 90% (non-condensing)

Display

Zoll	12.1 "
Auflösung Breite	800
Auflösung Höhe	600
Lumen	450 cd / m ²
Hintergrundbeleuchtung	LED
MTBF	50000 h ²
Farben	262000
Kontrast	700:1
Touchtypen	optional (e-Resistive / e-Capacitive / Projected Capacitive)

Mounting

VESA 75	x
Panel Befestigung	x
Tischständer	x