

Chassis Selection Guide

Model No.	Type	Board Type		max. Slots	Drive Capacity				Fan				Indicators		Front Panel Control				PSU	Dimensions (mm)			Color	
		Slot SBC	Motherboard		5.25" Ext	3.5" Ext	2.5" Int	3.5" Int	4cm	6cm	8cm	12cm	Power	HDD	Power	Reset	USB	Keylock		Depth	Height	Width	Black	White
RC-725	2U	PICMG 1.3 full-size		6	1	1		1			2		•	•	•	•		•	PS/2	420	88,2	427	•	
RC-730	3U		ATX, microATX, Mini-ITX	6	4	2		1		1	3*		•	•	•	•	2	•	PS/2	480	132	427	•	
RC-740-AT	4U	full-size		14	4	1		2			1	1	•	•	•	•	2	•	PS/2	480	176,8	427	•	
RC-740-ATX	4U		ATX, microATX, Mini-ITX	7	4	1		2				1	•	•	•	•	2	•	PS/2	480	176,8	427	•	
RC-741-AT	4U	full-size		14	2			8			2	1	•	•	•	•	2	•	PS/2	480	176,8	427	•	
RC-741-ATX	4U		ATX, microATX, Mini-ITX	7	2			8			3	1	•	•	•	•	2	•	PS/2	480	176,8	427	•	
PAC-106G	Comp	full-size		6		1		1			1		•	•	•	•	2		1U	400	175,5	166		•
PAC-1700G	Comp	full-size		7	1	1		2			1		•	•	•	•			PS/2	433	253,7	192,4	•	
PAC-53GH	Comp	half-size		3			1						•	•	•	•	2		1U	218	200	95		•
PAC-42GH	Comp	half-size		4		1*	2*	1*			1		•	•	•	•	2		1U	269	230	140		•
PR-1500G	Comp	half-size		5	1*	1		1			1		•	•	•	•	2		1U	254	132	286		•
EBC-3200	Emb		Mini-ITX	X			1		2				•	•	•	•	2		external	180	55	260	•	

*= Optional or specific - please refer to datasheet or contact us.
For further information please do not hesitate to contact us.

LEAD Deutschland GmbH
Widdersdorfer Str. 209
50825 Köln / Cologne

Tel: +49 (0) 221 / 95 47 9 - 0
Mail: info@lead.de
www.lead.de